

Technical Bulletin

Prowick Desolder Braid

DESCRIPTION

De-solder braid is pre-fluxed copper braid used to remove solder, which allows components to be replaced and excess solder to be removed. Generally the braid is supplied on static dissipative bobbins for static sensitive environments.

For the fastest wicking action, rosin flux coated braid is ideal for high volume PCB production/repair environments.

FEATURES & BENEFITS

- Rosin flux coated braid
- Fastest wicking action
- Exceeds MIL-F-14256 Type R
- Meets IPC Standard J-STD-004
- Anti Static Spool (except where indicated)

SIZE CHART

Colour Code	Width (in)	Width (mm)
White	0.035	0.9
Yellow	0.055	1.4
Green	0.075	1.9
Blue	0.098	2.5
Brown	0.130	3.3
Red	0.193	4.9

HEALTH & SAFETY

For detailed information refer to the Health and Safety Data Sheet (MSDS) available on request.



The information contained herein is based on data considered accurate and is offered at no charge. No warranty is expressed or implied regarding the accuracy of this data. Liability is expressly disclaimed for any loss or injury arising out of the use of this information or the use of the materials designated.

solderconnection.com

Unit 5 | Severn Link Distribution Centre
Chepstow | Monmouthshire | NP16 6UN

Revision No: 3
Revision Date: 26/05/26

sales@solderconnection.co.uk
Office: 01291 624 400